

知 路由器如何比较当前配置与保存配置是否一致

恢复出厂 刘嘉福 2020-02-12 发表

问题描述

在使用过程，保存了若干配置，如何确认这些配置的差异或当前配置与保存配置的差异？

解决方法

华为命令：<Huawei>compare configuration

```
<Huawei>compare configuration
Warning: The current configuration is not the same as the next startup configuration file. There may be several differences, and the following are some configurations beginning from the first:
===== Current configuration line 47 =====
interface LoopBack1
 ip address 2.2.2.2 255.255.255.255
#
user-interface con 0
user-interface vty 0 4
user-interface vty 16 20

===== Configuration file line 47 =====
user-interface con 0
user-interface vty 0 4
user-interface vty 16 20
#
return
```

华三命令：display diff configfile file-name-s { configfile file-name-d | current-configuration | startup-configuration }

```
display diff current-configuration { configfile file-name-d | startup-configuration }
display diff startup-configuration configfile file-name-d
```

```
[H3C]dis diff current-configuration startup-configuration
--- Current configuration
+++ Startup configuration
@@ -23,9 +23,6 @@
 interface LoopBack0
 ip address 1.1.1.1 255.255.255.255
#
-interface LoopBack1
- ip address 2.2.2.2 255.255.255.255
-#
 interface GigabitEthernet0/0
 port link-mode route
 combo enable copper
```