

知 S5130 syslog典型组网配置案例（与IMC的imcsyslogdm联动）

Info-center 韦家宁 2020-05-21 发表

组网及说明

为了能够实时的收取交换机的syslog信息，需要在交换机部署info-center，同时在IMC纳管相应的设备，即可实现实时收取交换机的syslog信息。

IMC版本为PLAT 7.3 E0506P03

S5130的版本如下：

H3C Comware Software, Version 7.1.070, Release 6127P01

Copyright (c) 2004-2019 New H3C Technologies Co., Ltd. All rights reserved.

H3C S5130S-52S-HI uptime is 37 weeks, 2 days, 0 hours, 8 minutes

Last reboot reason : User reboot

Boot image: flash:/s5130s_hi-cmw710-boot-r6127p01.bin

Boot image version: 7.1.070, Release 6127P01

Compiled Jul 10 2019 11:00:00

System image: flash:/s5130s_hi-cmw710-system-r6127p01.bin

System image version: 7.1.070, Release 6127P01

Compiled Jul 10 2019 11:00:00

Feature image(s) list:

flash:/s5130s_hi-cmw710-freeradius-r6127p01.bin, version: 7.1.070

Compiled Jul 10 2019 11:00:00

Slot 1:

Uptime is 37 weeks,2 days,0 hours,8 minutes

S5130S-52S-HI with 1 Processor

BOARD TYPE: S5130S-52S-HI

DRAM: 512M bytes

FLASH: 256M bytes

PCB 1 Version: VER.B

Bootrom Version: 130

CPLD 1 Version: 001

Release Version: H3C S5130S-52S-HI-6127P01

Patch Version : None

Reboot Cause : UserReboot

[SubSlot 0] 48GE+4SFP Plus

配置步骤

S5130 syslog部署：

info-center enable

info-center loghost 10.190.8.7

IMC纳管S5130交换机：



在IMC的“告警”-“syslog管理”-“浏览syslog”通过搜索设备的IP，即可看到该交换机发送上来的syslog：

时间	日志来源	源IP	描述	源IP来源	操作时间
2020-05-21 10:21:55	syslog	10.10.10.10	INFO: Syslog received from 10.10.10.10	10.10.10.10	2020-05-21 10:21:55
2020-05-21 10:21:56	syslog	10.10.10.10	INFO: Syslog received from 10.10.10.10	10.10.10.10	2020-05-21 10:21:56
2020-05-21 10:21:57	syslog	10.10.10.10	INFO: Syslog received from 10.10.10.10	10.10.10.10	2020-05-21 10:21:57
2020-05-21 10:21:58	syslog	10.10.10.10	INFO: Syslog received from 10.10.10.10	10.10.10.10	2020-05-21 10:21:58
2020-05-21 10:21:59	syslog	10.10.10.10	INFO: Syslog received from 10.10.10.10	10.10.10.10	2020-05-21 10:21:59

通过点击“描述”下的信息，可以查看到具体的syslog信息：

源IP	源IP来源	操作时间	描述
10.10.10.10	10.10.10.10	2020-05-21 10:21:55	INFO: Syslog received from 10.10.10.10
10.10.10.10	10.10.10.10	2020-05-21 10:21:56	INFO: Syslog received from 10.10.10.10
10.10.10.10	10.10.10.10	2020-05-21 10:21:57	INFO: Syslog received from 10.10.10.10
10.10.10.10	10.10.10.10	2020-05-21 10:21:58	INFO: Syslog received from 10.10.10.10
10.10.10.10	10.10.10.10	2020-05-21 10:21:59	INFO: Syslog received from 10.10.10.10

至此，S5130交换机syslog典型组网配置案例已完成！

配置关键点