

知 MSR5660在OSPF进程中添加静默端口报错问题解决方法

OSPF 王丽娟 2020-07-06 发表

问题描述

在MSR5660设备上配置OSPF静默端口时系统提示：OSPF Cannot be configured as a silent-interface in current process.

```
[H2B7-R1-MSR5660-ospf-1]silent-interface GigabitEthernet 2/0/2
OSPF Cannot be configured as a silent-interface in current process.
[H2B7-R1-MSR5660-ospf-1]dis this
#
ospf 1
#
return
```

解决方法

排查发现2/0/2接口加入了VPN实例1中，而VPN实例与非实例间路由及接口是隔离的，因此带VPN实例的接口只能在该实例OSPF进程中添加为静默端口。

```
#  
interface GigabitEthernet2/0/2  
port link-mode route  
combo enable copper  
ip binding vpn-instance 1  
ip address 1.1.1.1 255.255.255.0  
  
#  
在VPN实例1的OSPF 2进程中添加静默端口后解决。  
[H2B7-R1-MSR5660]ospf 2 vpn-instance 1  
[H2B7-R1-MSR5660-ospf-2]silent-interface GigabitEthernet 2/0/2  
[H2B7-R1-MSR5660-ospf-2]dis this  
#  
ospf 2 vpn-instance 1  
silent-interface GigabitEthernet2/0/2  
#
```