

知 S5820 telnet 单个用户登录数限制的典型组网配置案例

Telnet 韦家宁 2020-09-13 发表

组网及说明

本案例为S5820 telnet 单个用户登录数限制的典型组网配置，通过access-limit来实现单个用户不能同时登陆。

配置步骤

```
<H3C>sys
System View: return to User View with Ctrl+Z.
[H3C]sysname SW1
[SW1]vlan 10
[SW1-vlan10]quit
[SW1]int gi 1/0/1
[SW1-GigabitEthernet1/0/1]port link-type access
[SW1-GigabitEthernet1/0/1]port access vlan 10
[SW1-GigabitEthernet1/0/1]quit
[SW1]int vlan 10
[SW1-Vlan-interface10]ip address 192.168.200.110 24
[SW1-Vlan-interface10]quit
[SW1]telnet server enable
[SW1]local-user admin
New local user added.
[SW1-luser-manage-admin]password simple admin
[SW1-luser-manage-admin]service-type ssh telnet terminal
[SW1-luser-manage-admin]authorization-attribute user-role network-admin
[SW1-luser-manage-admin]access-limit 1 //限制admin用户只能同时登陆一个，不能同时登陆多个
[SW1-luser-manage-admin]quit
[SW1]user-interface vty 0 63
[SW1-line-vty0-63]authentication-mode scheme
[SW1-line-vty0-63]quit
```

配置关键点

测试效果见附件！

附件下载：S5820 telnet 单个用户登录数限制的典型组网配置案例.rar