

知 S10510 WEB 单个用户登录数限制的典型组网配置案例

产品特性 韦家宁 2020-09-13 发表

组网及说明

详本案例为S10510 WEB 单个用户登录数限制的典型组网配置，通过access-limit来实现单个用户不能同时登陆。

S10510的版本信息如下：

```
H3C Comware Software, Version 7.1.070, Release 7536P05
Copyright (c) 2004-2017 New H3C Technologies Co., Ltd. All rights reserved.
H3C S10510 uptime is 92 weeks, 2 days, 4 hours, 3 minutes
Last reboot reason : USER reboot
Boot image: flash:/S10500-CMW710-BOOT-R7536P05.bin
Boot image version: 7.1.070, Release 7536P05
  Compiled Mar 28 2017 16:00:00
System image: flash:/S10500-CMW710-SYSTEM-R7536P05.bin
System image version: 7.1.070, Release 7536P05
  Compiled Mar 28 2017 16:00:00
```

配置步骤

```
<H3C>sys
System View: return to User View with Ctrl+Z.
[H3C]sysname SW1
[SW1]int vlan 1
[SW1-Vlan-interface1]ip address 192.168.200.110 24
[SW1-Vlan-interface1]quit
[SW1]ip http enable
[SW1]ip https enable
[SW1]local-user admin
New local user added.
[SW1-luser-manage-admin]password simple admin
[SW1-luser-manage-admin]service-type http https
[SW1-luser-manage-admin]authorization-attribute user-role network-admin
[SW1-luser-manage-admin]access-limit 1 //限制admin用户只能同时登陆一个，不能同时登陆多个
[SW1-luser-manage-admin]quit
```

配置关键点

测试结果见附件！

附件下载：S10510 WEB 单个用户登录数限制的典型组网配置案例.rar