

组网及说明

为了确保设备的WEB安全登陆管理，需对WEB进行登录限制。

S6520版本信息如下：

H3C Comware Software, Version 7.1.070, Release 1110P02

Copyright (c) 2004-2018 New H3C Technologies Co., Ltd. All rights reserved.

H3C S6520X-54QC-EI uptime is 30 weeks, 3 days, 14 hours, 55 minutes

Last reboot reason : Cold reboot

配置步骤

配置ACL对WEB进行登录限制：

1、开启HTTP HTTPS功能

```
[H3C]ip http enable
```

```
[H3C]ip https enable
```

2、创建用户名、密码，并赋予HTTP HTTPS的权限

```
[H3C]local-user admin
```

```
[H3C-luser-manage-admin]password simple admin
```

```
[H3C-luser-manage-admin]service-type http https
```

```
[H3C-luser-manage-admin]authorization-attribute user-role network-admin
```

```
[H3C-luser-manage-admin]quit
```

3、创建ACL，并应用到HTTP HTTPS

```
[H3C]acl basic 2000
```

```
[H3C-acl-ipv4-basic-2000]rule 0 permit source 192.168.10.2 0 //仅允许192.168.2.0这个主机通
```

过

```
[H3C-acl-ipv4-basic-2000]quit
```

```
[H3C]ip http acl 2000
```

```
[H3C]ip https acl 2000
```

配置关键点

附件下载：S6520 WEB登陆限制案例.zip