

知 S12508高危端口封堵配置案例

ACL 韦家宁 2020-09-18 发表

组网及说明

为了进一步保证设备安全，需配置ACL对高危端口进行拦截

S12508的版本信息如下：

H3C Comware Platform Software

Comware Software, Version 5.20, Release 1828P05

Copyright (c) 2004-2014 Hangzhou H3C Tech. Co., Ltd. All rights reserved.

H3C S12508 uptime is 58 weeks, 4 days, 9 hours, 34 minutes

Last reboot reason : User reboot

配置步骤

1、创建ACL，对高危端口进行拦截：

acl number 3210

rule 0 deny tcp destination-port eq 135

rule 1 deny udp destination-port eq 135

rule 2 deny tcp destination-port eq 137

rule 3 deny udp destination-port eq netbios-ns

rule 4 deny tcp destination-port eq 138

rule 5 deny udp destination-port eq netbios-dgm

rule 6 deny udp destination-port eq netbios-ssn

rule 7 deny tcp destination-port eq 139

rule 8 deny tcp destination-port eq 445

rule 9 deny udp destination-port eq 445

rule 10 deny tcp destination-port eq 3389

rule 11 deny udp destination-port eq 3389

rule 20 deny tcp source-port eq 135

rule 21 deny udp source-port eq 135

rule 22 deny tcp source-port eq 137

rule 23 deny udp source-port eq netbios-ns

rule 24 deny tcp source-port eq 138

rule 25 deny udp source-port eq netbios-dgm

rule 26 deny udp source-port eq netbios-ssn

rule 27 deny tcp source-port eq 139

rule 28 deny tcp source-port eq 445

rule 29 deny udp source-port eq 445

rule 30 deny tcp source-port eq 3389

rule 31 deny udp source-port eq 3389

rule 1500 permit ip

2、将ACL下发到端口：

int range gi 1/0/1 gi 1/0/24

packet-filter 3210 inbound

packet-filter 3210 outbound

quit

配置关键点