

知 动态路由下的不同VPN实例之间的路由互引

VRF 孔德飞 2022-03-16 发表


组网及说明

组网如图：

FW与MSR2建立OSPF邻居，与MSR2直连

FW的g1/0/1属于vpn1，g1/0/2属于VPN2

需求，通过动态路由的VPN互引实现MSR3的2.2.2.1可以访问MSR2的11.11.11.11



配置步骤

主要配置:

MSR2

```
interface GigabitEthernet0/0
port link-mode route
combo enable copper
ip address 1.1.1.1 255.255.255.0
```

ospf 1

```
import-route direct
area 0.0.0.0
network 1.1.1.0 0.0.0.255
```

```
ip route-static 2.2.2.0 24 1.1.1.2
```

FW

```
ip vpn-instance vpn1
address-family ipv4
route-replicate from vpn-instance vpn2 protocol direct
```

```
ip vpn-instance vpn2
address-family ipv4
route-replicate from vpn-instance vpn1 protocol direct advertise
route-replicate from vpn-instance vpn1 protocol ospf 1 advertise
```

```
ospf 1 vpn-instance vpn1
area 0.0.0.0
network 1.1.1.0 0.0.0.255
```

```
interface GigabitEthernet1/0/1
port link-mode route
combo enable copper
ip binding vpn-instance vpn1
ip address 1.1.1.2 255.255.255.0
```

```
interface GigabitEthernet1/0/2
port link-mode route
combo enable copper
ip binding vpn-instance vpn2
ip address 2.2.2.2 255.255.255.128
```

```
interface GigabitEthernet1/0/21
port link-mode route
combo enable copper
```

```
interface GigabitEthernet1/0/22
port link-mode route
combo enable copper
```

```
security-zone name Trust
import interface GigabitEthernet1/0/1
```

```
security-zone name Untrust
import interface GigabitEthernet1/0/2
```

```
security-policy ip
rule 0 name 0
action pass
```

```
vrf vpn1
rule 1 name 1
action pass
```

配置关键点

配置关键点:

```
route-replicate from { public | vpn-instance vpn-instance name } protocol
{ direct | static | { isis | ospf | rip } process-id } [advertise ]
```

MSR2

在vpn实例的视图下配置

忽略RT值(即VPN实例中不手工指定RT值)，将公网或其他VPN实例的路由信息引入到指定VPN实例中

```
undo enable copper
```

```
ip address 2.2.2.1 255.255.255.0
```

特别说明一点，公网的VPN有自己的VPN实例

```
ip route-static 1.0 24 2.2.2.2
```

```
ip route-static 11.11.11.0 24 2.2.2.2
```