

知 某局点S9505 V5设备忘记console登录密码

console 刘倩 2023-02-21 发表

组网及说明

组网不涉及

告警信息

不涉及告警

问题描述

V5设备忘记console登录密码。

过程分析

见具体解决办法

解决方法

可以按下面方法使得console端口密码不生效，设备重启后修改console端口的密码并save配置文件，再次重启新的密码生效，该功能在1273及以后版本才能支持。

```
S9500>reboot
This command will reboot the system. The current configuration has not been saved and will be lost if you continue. Continue? [Y/N] y
ZBB_TEST
Starting...
*****
*   *   *
*   H3C S9500 Bootrom, Version 206   *
*   *   *
*****
Copyright(C) 2004-2007 Hangzhou H3C Technologies Co., Ltd.
Creation date: Dec 28 2004, 10:37:14

CPU type      : MPC755
CPU L2 Cache  : 1024KB
CPU Clock Speed : 400MHz
BUS Clock Speed : 100MHz
Memory Size   : 512MB
```

Flash file system init....done

```
Board self testing.....  
The board is steady  
SlotNo of this board is 0  
The MCX is existent  
BootRom main system CRC check is OK  
82559 register testing is OK  
EPLD1 testing is OK  
EPLD2 testing is OK  
16c2552 register testing is OK  
Please check LEDs.....LED testing finished  
The switch's Mac address is 00e0.fc3a.076f
```

Press Ctrl+B to enter Boot Menu... 5

```
password:  
MAIN MENU
```

- 1. Boot with default mode
- 2. Boot from Flash
- 3. Boot from CF card
- 4. Enter serial submenu
- 5. Enter ethernet submenu
- 6. Modify Flash description area
- 7. Modify bootrom password
- 0. Reboot

Enter your choice(0-7): 5

ETHERNET SUBMENU

- 1. Download file to SDRAM through ethernet interface and boot
- 2. Download file to Flash through ethernet interface
- 3. Download file to CF card through ethernet interface
- 4. Modify ethernet interface boot parameter
- 0. Return to main menu

Be sure to select 4 to modify boot parameter before downloading!

Enter your choice(0-4): 4

Note: Two protocols for download, tftp & ftp.
You can modify the flags following the menu.
tftp=0x80, ftp=0x0.

:= clear field; '-' = go to previous field; ^D = quit

```
boot device      : fei0
processor number : 0
host name       : 9500
file name        : S9500-VRP310-R1271P01-SI.app
inet on ethernet (e) : 10.11.113.155
inet on backplane (b):
host inet (h)   : 10.11.113.188
gateway inet (g) :
user (u)         : 95
ftp password (pw) (blank = use rsh): 95
flags (f)        : 0x00x20 B需要把flag标识修改成0x20
target name (tn) :
startup script (s) :
other (o)        :
```

Write flash...done!

ETHERNET SUBMENU

1. Download file to SDRAM through ethernet interface and boot