Nimble主机实施：FC存储部署和测试

主机相关　**车公子啊**　2023-11-03 发表

组网及说明

存储设备：HPE Alletra 6070；主机设备：ilo 5，OS：RHEL7u9

（1）首先在主机端使用cat /sys/class/fc_host/hostX/port_name确认HBA WWPN。

（2）然后在存储端使用fc --list确认存储端WWPN。

（3）配置好ZONE之后在存储端使用fc --info确认主机已经正常登录到存储。

（4）在存储管理界面点击MANAGE-DATA ACCESS中的"+"号创建INITIATOR GROUP。
输入INITIATOR GROUP NAME，点击ADD添加INITIATOR并关联正确的主机HBA WWPN。

（5）点击MANAGE-DATA STORAGE中的"+"号创建卷。

（6）在主机端使用ncmadm --fcrescan对HBA进行扫描，然后使用ncmadm –确认LUN已经被扫描到
，并使用multipath –ll确认多路径已经配置完成。

```
[root@cpzclabhost-rhel7 host2]# ncmadm --fcrescan
Fc rescan initiated
[root@cpzclabhost-rhel7 host2]# cd
[root@cpzclabhost-rhel7 ~]# ncmadm -l
size=1.0G uuid=204608aaf11d80d876c9ce90088ba0af8 mount-device: /dev/nimblestorage/ccc-204608aaf11d80d876c9ce90088ba0af8
  + array_id=1 device=/dev/dm-9 sync_replicated=no
  |-    1:0:4:1   sde   8:64  dev_st=running    dm_st=active      chk_st=ready
  |-    1:0:7:1   sdf   8:80  dev_st=running    dm_st=active      chk_st=ready
size=3.0G uuid=2fb11ff1145f814de6c9ce900850cbd49 mount-device: /dev/nimblestorage/ilo1vv-2fb11ff1145f814de6c9ce900850cb
d49
target: iqn.2007-11.com.nimblestorage:cpzccs3kgrp01-g52e143b81b5c4f3d connection_mode=manual
  + array_id=1 device=/dev/dm-8 sync_replicated=no
```