

问题描述

SQLSERVER 如何进行差异备份恢复

解决方法

说明：以下示例首先显示如何使用 BACKUP 语句来创建 AdventureWorks2022 数据库的完整数据库备份和差异数据库备份。然后按顺序还原这些备份。将数据库还原到完成差异数据库备份时的状态。

```
USE master;
--Make sure the database is using the simple recovery model.
ALTER DATABASE AdventureWorks2022 SET RECOVERY SIMPLE;
GO
-- Back up the full AdventureWorks2022 database.
BACKUP DATABASE AdventureWorks2022
TO DISK = 'Z:\SQLServerBackups\AdventureWorks2022.bak'
WITH FORMAT;
GO
--Create a differential database backup.
BACKUP DATABASE AdventureWorks2022
TO DISK = 'Z:\SQLServerBackups\AdventureWorks2022.bak'
WITH DIFFERENTIAL;
GO
--Restore the full database backup (from backup set 1).
RESTORE DATABASE AdventureWorks2022
FROM DISK = 'Z:\SQLServerBackups\AdventureWorks2022.bak'
WITH FILE=1, NORECOVERY;
--Restore the differential backup (from backup set 2).
RESTORE DATABASE AdventureWorks2022
FROM DISK = 'Z:\SQLServerBackups\AdventureWorks2022.bak'
WITH FILE=2, RECOVERY;
GO
```