

短 无线协议规定的802.11 Deauth报文的Reason Code

wlan接入 朱恺 2017-12-29 发表

Code	Reason
0	Reserved
1	Unspecific Reason
2	Previous authentication no longer valid
3	Deauthenticated because sending STA is leaving (or has left) IBSS or ESS
4	Disassociated due to inactivity
5	Disassociated because AP is unable to handle all currently associated STAs
6	Class 2 frame received from nonauthenticated STA
7	Class 3 frame received from nonassociated STA
8	Disassociated because sending STA is leaving (or has left) BSS
9	STA requesting (re)association is not authenticated with responding STA
10	Disassociated because the information in the Power Capability element is unacceptable
11	Disassociated because the information in the Supported Channels element is unacceptable
12	Reserved
13	Invalid information element.
14	Message integrity code (MIC) failure
15	4-Way Handshake timeout
16	Group Key Handshake timeout
17	Information element in 4-Way Handshake different from (Re)Association Request/Probe Response/Beacon frame
18	Invalid group cipher or Association denied due to requesting STA not supporting all of the data rates in the BSSBasicRateSet parameter
19	Invalid pairwise cipher
20	Invalid AKMP
21	Unsupported RSN information element version
22	Invalid RSN information element capabilities
23	IEEE 802.1X authentication failed
24	Cipher suite rejected because of the security policy
25-31	Reserved
32	Disassociated for unspecified, QoS-related reason
33	Disassociated because QoS AP lacks sufficient bandwidth for this QoS STA
34	Disassociated because excessive number of frames need to be acknowledged, but are not acknowledged due to AP transmissions and/or pel conditions
35	Disassociated because STA is transmitting outside the limits of its TXOPs
36	Requested from peer STA as the STA is leaving the BSS (or resetting)
37	Requested from peer STA as it does not want to use the mechanism
38	Requested from peer STA as the STA received frames using the mechanism for which a setup is required
39	Requested from peer STA due to timeout
45	Peer STA does not support the requested cipher suite
45-65	Reserved
535	Reserved