

知 S7000/S7500E/10500系列（V5）交换机启动过程Console信息显示说明

console

zhiliao_pdGY6

2018-11-26 发表

组网及说明

1 配置需求和说明

把设备的Console线给接上，然后给设备上电，查看设备启动过程显示的信息。本案例以S3600V2-28TP-EI举例。

2 组网图

无

配置步骤

3启动过程信息

Starting.....

Press Ctrl+D to access BASIC BOOT MENU

```
*****
*                                     *
*      H3C S3600V2-28TP-EI BOOTROM, Version 133      *
*                                     *
*****
```

Copyright (c) 2004-2017 New H3C Technologies Co., Ltd.

Creation Date : Apr 5 2017, 13:49:31

CPU Clock Speed : 600MHz

Memory Size : 256MB

Flash Size : 128MB

CPLD Version : 001

PCB Version : Ver.A

Mac Address : 586ab1710285

Press Ctrl-B to enter Extended Boot menu...0

Starting to get the main application file--flash:/S3600V2_E-CMW520-R2112.bin!..

```
.....
.....
.....
```

The main application file is self-decompressing.....

```
.....
.....
.....
.....
.....
.....
.....
.....
.....
.....
.....
```

.....Done!

System is starting...

Startup configuration file does not exist.

It will take a long time to get configuration file, please wait...

Press CTRL_C to break

Retrieving configuration file failed!

User interface aux1 is available.

Press ENTER to get started.

<H3C>

#Jan 1 00:05:26:401 2010 H3C SHELL/4/LOGIN:

Trap 1.3.6.1.4.1.2011.10.2.2.1.1.3.0.1<h3cLogIn>: login from Console

%Jan 1 00:05:26:542 2010 H3C SHELL/5/SHELL_LOGIN: Console logged in from aux1.

<H3C>

<H3C>

说明：如下三行日志是提示有用户从Console登录。

#Jan 1 00:05:26:401 2010 H3C SHELL/4/LOGIN:

Trap 1.3.6.1.4.1.2011.10.2.2.1.1.3.0.1<h3cLogIn>: login from Console

%Jan 1 00:05:26:542 2010 H3C SHELL/5/SHELL_LOGIN: Console logged in from aux1.

配置关键点