

Comware V5平台MSR路由器怎么恢复出厂设置?

恢复出厂 骆翔 2018-12-25 发表

问题描述

Comware V5平台MSR路由器怎么恢复出厂设置?

解决方法

1. 命令行恢复出厂设置

<Sysname> reset saved-configuration

The saved configuration file will be erased. Are you sure? [Y/N]:y

Configuration file in flash is being cleared.

Please wait

Configuration file is cleared.

<H3C>reboot //重启设备

Start to check configuration with next startup configuration file, please wait.....DONE!

This command will reboot the device. Current configuration will be lost, save current configuration? [

Y/N]:n //是否保存当前配置, 此处选择n

This command will reboot the device. Continue? [Y/N]:y //是否要继续重启设备, 选择y

#Jan 1 00:23:20:782 2013 H3C DEVM/1/REBOOT:

Reboot device by command.

%Jan 1 00:23:20:782 2013 H3C DEVM/5/SYSTEM_REBOOT: System is rebooting now.

Now rebooting, please wait...

<H3C>

System is starting... //提示系统正在启动, 重启之后系统即恢复成出厂配置

2. WEB界面恢复出厂设置

在导航栏中选择“系统管理 > 配置管理”，选择“初始化”，单击“恢复出厂设置”按钮。



系统会提示本次操作将把设备恢复到运营商的出厂设置，并导致设备重启，是否继续，选择“确定”后，设备会自动重启并恢复至出厂配置。

