

知 如何查看T300终端的RSSI值?

物联网

姚超飞 2018-12-29 发表

问题描述

如何查看物联网终端的RSSI值?

解决方法

Probe (进入ap的隐藏视图)

debugging wlan rfid-tracking

debug信息如下: ap收集到物联网上报的数据后, 将报文打包发送给服务器计算, 报文的倒数第二个字符是物联网终端的RSSI值。

<ap1>t d

The current terminal is enabled to display debugging logs.

<ap1>t m

The current terminal is enabled to display logs.

<ap1>*Dec 26 09:03:04:220 2018 ap1 WLOC/7/PACKET: IOT received a IoT packet , length 13. packet detail:

01(moudle 1) 01 01 20 83 41 8b fb bf 63 09(SN) 38(rssi) 04

*Dec 26 09:03:04:220 2018 ap1 WLOC/7/PACKET: IOT received a IoT packet , length 13. packet detail:

02 01 01 20 83 41 8b fb bf 63 09 35 04

*Dec 26 09:03:04:287 2018 ap1 WLOC/7/PACKET: IOT sent a IoT packet , length 140. packet detail:

63 96 2b 14 32 31 30 32 33 35 41 31 4a 4d 43 31

35 42 30 30 30 30 34 33 14 32 31 39 38 30 31 41

31 35 4b 38 31 37 42 45 30 30 36 31 39 06 00 06

38 39 35 31 32 39 01 0c 83 41 72 49 78 ed 10 00

02 01 3f 04 02 0c 83 41 72 49 78 ed 10 00 02 01

36 04 01 0c 83 41 97 47 5d f7 10 00 02 01 37 04

02 0c 83 41 97 47 5d f7 10 00 02 01 42 04 01 0c

83 41 8b fb bf 63 10 00 02 01 38 04 02 0c 83 41

8b fb bf 63 10 00 02 01 35 04 01 4b