

知 SFP+光模块的外观及详细参数？

光模块 樊凡 2019-01-01 发表

问题描述

SFP+光模块的外观及详细参数？

解决方法

外观：



参数：

对外型号	中心波长 (nm)	Fiber Mode	光纤直径 (μm)	模式带宽 (MHz*km)	传输距离	传输速率	接口指标 (dBm)	
							输出光功率	接收光功率
SFP-XG-SX-M850-A	850	MMF	50/125	2000	300m	10.31Gbps	-7.3~-1	-9.9~+0.5
				500	82m			
				400	66m			
			62.5/125	200	33m			
				160	26m			
SFP-XG-SX-M850-B (已停产)	850	MMF	50/125	2000	100m	10.31Gbps	-7.3~-1	-9.9~+0.5
				500	25m			
				400	20m			
			62.5/125	200	10m			
				160	8m			
SFP-XG-SX-M850-D	850	MMF	50/125	2000	300m	10.31Gbps	-7.3~-1	-9.9~+0.5
				500	82m			
				400	66m			
			62.5/125	200	33m			
				160	26m			
SFP-XG-SX-M850-E	850	MMF	50/125	2000	300m	10.31Gbps	-7.3~-1	-9.9~+0.5
				500	82m			
				400	66m			
			62.5/125	200	33m			
				160	26m			
SFP-XG-SX-M850-F1	850	MMF	50/125	2000	300m	10.31Gbps	-7.3~-1	-9.9~+0.5
				500	82m			
				400	66m			
			62.5/125	200	33m			
				160	26m			
SFP-XG-LX220-MM1310	1310	MMF	50/125	1500	220m	10.31Gbps	-6.5~+0.5	-6.5~+1.5
				500	220m			
				400	100m			
			62.5/125	200	220m			
				160	220m			
SFP-XG-LX-SM1310	1310	SMF	9/125	-	10km	10.31Gbps	-8.2~+0.5	-14.4~+0.5
SFP-XG-LX-SM1310-D	1310	SMF	9/125	-	10km	10.31Gbps	-8.2~+0.5	-14.4~+0.5
SFP-XG-LX-SM1310-E	1310	SMF	9/125	-	10km	10.31Gbps	-8.2~+0.5	-14.4~+0.5
SFP-XG-LH40-SM1550	1550	SMF	9/125	-	40km	10.31Gbps	-4.7~+4	-15.8~-1
SFP-XG-LH40-SM1550-D	1550	SMF	9/125	-	40km	10.31Gbps	-4.7~+4	-15.8~-1
SFP-XG-LH80-SM1550	1550	SMF	9/125	-	80km	10.31Gbps	0~+4	-24~-7
SFP-XG-LH80-SM1550-D	1550	SMF	9/125	-	80km	10.31Gbps	0~+4	-24~-7

对外型号	中心波长 (nm)	Fiber Mode	光纤直径 (μm)	模式带宽 (MHz*km)	传输距离	传输速率	接口指标 (dBm)	
							输出光功率	接收光功率
SFP-FC-8G-SW-MM850	850	MMF	62.5/125	200	150m	2.125Gbps	-10 ~ 0	-13.1 ~ 0
				500	380m	4.25Gbps	-9 ~ 0	-12.1 ~ 0
				2000	500m	8.5Gbps	-8.2 ~ 0	-11.2 ~ 0
SFP-FC-8G-LW-SM1310	1310	SMF	9/125	-	10km	2.125Gbps	-9.5 ~ -3	-18.2 ~ -3
						4.25Gbps	-8.4 ~ -1	-15.4 ~ -1
						8.5Gbps	-8.4 ~ +0.5	-13.8 ~ +0.5
SFP-XG-LH80-Tunable	1528.773 ~ 1566.723	SMF	9/125	-	80km	9.95 ~ 11.3 Gbps	-1 ~ +3	-24 ~ -7