

知 设备如何进行ping测试?

Ping

骆翔 2019-01-03 发表

问题描述

设备如何进行ping测试?

设备如何进行Tracert测试?

解决方法

使用ping命令可以测试网络的连通性

```
<H3C>ping 10.88.18.181
```

```
PING 10.88.18.181: 56 data bytes, press CTRL_C to break
```

```
Reply from 10.88.18.181: bytes=56 Sequence=0 ttl=128 time=2 ms
```

```
Reply from 10.88.18.181: bytes=56 Sequence=1 ttl=128 time=3 ms
```

```
Reply from 10.88.18.181: bytes=56 Sequence=2 ttl=128 time=2 ms
```

```
Reply from 10.88.18.181: bytes=56 Sequence=3 ttl=128 time=2 ms
```

```
Reply from 10.88.18.181: bytes=56 Sequence=4 ttl=128 time=2 ms
```

```
--- 10.88.18.181 ping statistics ---
```

```
5 packet(s) transmitted
```

```
5 packet(s) received
```

```
0.00% packet loss
```

```
round-trip min/avg/max = 2/2/3 ms
```

使用tracert命令可以追踪路由

```
<H3C>tracert 10.88.18.181
```

```
traceroute to 10.88.18.181(10.88.18.181) 30 hops max,40 bytes packet, press CTRL_C to break
```

```
1 10.88.18.181 1 ms * 2 ms
```