


V7防火墙文件txt文件过滤典型配置

文件过滤 数据过滤 冉博文 2015-12-31 发表

客户在上网过程中，不想通过FTP或者http方式进行对TXT文件内容的上传和下载，在阻断的同时还要记录相关的阻断日志。



配置接口IP地址

```
#  
interface GigabitEthernet4/0/5  
port link-mode route  
ip address 192.168.1.1 255.255.255.0  
application statistics enable inbound  
application statistics enable outbound  
#  
interface GigabitEthernet4/0/9  
port link-mode route  
ip address 192.168.207.11 255.255.254.0  
nat outbound 2000  
application statistics enable inbound  
application statistics enable outbound
```

#

将接口加入安全域

#

```
security-zone name Trust  
import interface GigabitEthernet4/0/5  
#  
security-zone name Untrust  
import interface GigabitEthernet4/0/9
```

acl advanced 3000

rule 0 permit ip

#

配置文件过滤组，匹配文本txt

#

file-filter filetype-group fg

pattern fg1 text txt

#

配置文件过滤策略，配置两条过滤规则，其中一个匹配http类型，另外一个匹配ftp类型

#

file-filter policy fp

rule r1

 filetype-group fg

 application type http

 direction both

 action drop logging

rule r2

 filetype-group fg

 application type ftp

 direction both

 action drop logging

```
#  
配置app-profile且绑定文件过滤策略  
#  
app-profile fp_profile  
file-filter apply policy fp  
#  
配置对象组策略，且深度检测  
#  
object-policy ip Trust-Untrust  
rule 1 inspect fp_profile  
  
#  
配置域间策略，  
#  
zone-pair security source Trust destination Untrust  
object-policy apply ip Trust-Untrust  
#  
  
zone-pair security source Untrust destination Trust  
object-policy apply ip Untrust-Trust  
#  
激活配置  
#  
[H3C]inspect activate
```

在域间策略里调用并在全局激活。