

知 "The stp info of Instance 0's Ethernet1/0/1 has aged out because of not receiving message!"提示信息的含义

岳斌 2007-12-17 发表

当交换机上出现如下Trap信息时:

```
%Apr 2 01:15:01:613 2000 H3C MSTP/3/AGEDOUT:- 1 -The stp info of Instance 0's Ethernet1/0/1 has aged out because of not receiving message!
```

```
%Apr 2 01:15:01:778 2000 H3C MSTP/3/AGEDOUT:- 1 -The stp info of Instance 0's Ethernet1/0/2 has aged out because of not receiving message!
```

```
%Apr 2 01:15:01:948 2000 H3C MSTP/3/AGEDOUT:- 1 -The stp info of Instance 0's Ethernet1/0/5 has aged out because of not receiving message!
```

```
%Apr 2 01:15:02:118 2000 H3C MSTP/3/AGEDOUT:- 1 -The stp info of Instance 0's Ethernet1/0/6 has aged out because of not receiving message!
```

说明这些端口接收到的BPDU已经超时了, 一般这个时间是18秒我们会提示超时, 然后会重新计算生成树!

需要注意的是, 当端口配置了环路检测"loopback-detection"并检测到环路时, 不一定会出现该提示信息, 因为检测到环路后端口会清空mac表项并在一段时间内不转发报文, 但不会不接收和发送bpdu报文。