

Sanclient软件不能发现FC客户端的解决方法

一 组网:

无

二 问题描述:

在sanclient中查看服务器, 报以下红字部份错误

```
# ./sanclient monitor
```

```
SAN Client v4.50 (build 907)
```

```
Copyright 2001-2006 by FalconStor. All Rights Reserved.
```

```
Select an item:
```

```
0. < Quit >
```

```
1. List SAN Client Configuration
```

```
2. List SAN Devices
```

```
3. Add Storage Servers
```

```
4. Delete Storage Servers
```

```
5. Rescan SAN Devices
```

```
6. Attach SAN Devices
```

```
7. Detach SAN Devices
```

```
8. Enable Protocol
```

```
9. Disable Protocol
```

```
10. View Configured Protocol
```

```
Choose a number: 1
```

```
Failed to connect to client daemon at p630, 0
```

```
Configured Server(s) on client localhost:
```

```
Server : h3c-NeoStor
```

```
Invalid shandle -1
```

```
Failed to get Fibre Channel device count of server h3c-NeoStor, -13
```

```
Client daemon is not connected!
```

三 过程分析:

无

四 解决方法:

#vi /etc/hosts文件, 确认以下红色字符串是否正确, 如果没有, 则添加该字符串

```
127.0.0.1 localhost loopback p630 # loopback (lo0) name/address
```

```
200.200.0.134 p630
```