

DOM卡中apache日志超大解决办法

一、组网需求:

无

二、组网图:

无

三、配置步骤:

- 1) 进入apache配置目录: cd /usr/local/apache-tomcat-5.5.12/conf
- 2) 备份: cp ./logging.properties ./logging.properties.bak
- 2) 编辑apache的日志配置文件: vi logging.properties
- 3) 将所有的level设置为 OFF; 最终结果如下:

```
handlers=1catalina.org.apache.juli.FileHandler, 2localhost.org.apach
e.juli.FileHandler, 3manager.org.apache.juli.FileHandler,
4admin.org.apache.juli.FileHandler, 5host-
manager.org.apache.juli.FileHandler,
java.util.logging.ConsoleHandler
.handlers=1catalina.org.apache.juli.FileHandler, java.util.logging.Con
soleHandler
#####
###
# Handler specific properties.
# Describes specific configuration info for Handlers.
#####
###
1catalina.org.apache.juli.FileHandler.level = OFF
1catalina.org.apache.juli.FileHandler.directory =
${catalina.base}/logs
1catalina.org.apache.juli.FileHandler.prefix = catalina.
2localhost.org.apache.juli.FileHandler.level = OFF
2localhost.org.apache.juli.FileHandler.directory =
${catalina.base}/logs
2localhost.org.apache.juli.FileHandler.prefix = localhost.
3manager.org.apache.juli.FileHandler.level = OFF
3manager.org.apache.juli.FileHandler.directory =
${catalina.base}/logs
3manager.org.apache.juli.FileHandler.prefix = manager.
4admin.org.apache.juli.FileHandler.level = OFF
4admin.org.apache.juli.FileHandler.directory = ${catalina.base}/logs
4admin.org.apache.juli.FileHandler.prefix = admin.
5host-manager.org.apache.juli.FileHandler.level = OFF
5host-manager.org.apache.juli.FileHandler.directory = ${catalina.bas
e}/logs
5host-manager.org.apache.juli.FileHandler.prefix = host-manager.
java.util.logging.ConsoleHandler.level = OFF
java.util.logging.ConsoleHandler.formatter =
java.util.logging.SimpleFormatter
#####
###
# Facility specific properties.
# Provides extra control for each logger.
#####
###
org.apache.catalina.core.ContainerBase.[Catalina].[localhost].level =
OFF
org.apache.catalina.core.ContainerBase.[Catalina].
[localhost].handlers = 2localhost.org.apache.juli.FileHandler
org.apache.catalina.core.ContainerBase.[Catalina].[localhost].[mana
ger].level = OFF
```

```
org.apache.catalina.core.ContainerBase.[Catalina].[localhost].[/manager].handlers = 3manager.org.apache.juli.FileHandler
org.apache.catalina.core.ContainerBase.[Catalina].[localhost].[/admin].level = OFF
org.apache.catalina.core.ContainerBase.[Catalina].[localhost].[/admin].handlers = 4admin.org.apache.juli.FileHandler
org.apache.catalina.core.ContainerBase.[Catalina].[localhost].[/host-manager].level = OFF
org.apache.catalina.core.ContainerBase.[Catalina].[localhost].[/host-manager].handlers = 5host-manager.org.apache.juli.FileHandler
# For example, set the com.xyz.foo logger to only log SEVERE
# messages:
#org.apache.catalina.startup.ContextConfig.level = FINE
```

4) 保存退出:

5)在/usr/local/apache-tomcat-5.5.12/bin目录下执

行: ../bin/shutdown.sh;../bin/startup.sh

6) 进入/usr/local/apache-tomcat-5.5.12/logs, 执行ll -h查看日志文件应该已被限制在大小为0状态;

四、配置关键点:

无