

SR6600路由器MPLS L3VPN 及 静态路由配置


关键词：SR66;MPLS;BGP;VPN;静态路由

一、组网需求：

2台PE各接着一个vpna的站点，PEA连接vpna站点1出口CEA，PEA与CEA通过静态路由访问CEA下挂站点

设备清单：SR6600路由器3台

二、组网图：



三、配置步骤：

设备和版本：SR6600

CEA配置：

```
interface Ethernet0/0
port link-mode route
ip address 192.168.0.2 255.255.255.0
#
interface Ethernet0/1
port link-mode route
ip address 192.168.1.1 255.255.255.0
#
ip route-static 0.0.0.0 0.0.0.0 192.168.0.1
#
```

PEA配置：

```
router id 1.1.1.1
#
ip vpn-instance vpna
route-distinguisher 1:1
vpn-target 1:1 export-extcommunity
vpn-target 1:1 import-extcommunity
#
mpls lsr-id 1.1.1.1
#
mpls
#
mpls ldp
```

```
#  
interface Ethernet0/0  
port link-mode route  
ip address 1.2.0.1 255.255.255.0  
mpls  
mpls ldp  
#  
interface Ethernet0/1  
port link-mode route  
ip binding vpn-instance vpna  
ip address 192.168.0.1 255.255.255.0  
rip version 2 multicast  
#  
interface LoopBack0  
ip address 1.1.1.1 255.255.255.255  
#  
bgp 1  
undo synchronization  
group 1 internal  
peer 1 connect-interface LoopBack0  
peer 2.2.2.2 group 1  
#  
ipv4-family vpnv4  
peer 1 enable  
peer 2.2.2.2 enable  
peer 2.2.2.2 group 1  
#  
ipv4-family vpn-instance vpna  
network 192.168.0.0  
import-route static  
#  
ospf 1  
area 0.0.0.0  
network 1.1.1.1 0.0.0.0  
network 1.2.0.0 0.0.0.255  
#  
ip route-static vpn-instance vpna 192.168.1.0 255.255.255.0 192.168.0.2  
#  
PEB配置:  
#  
router id 2.2.2.2  
#  
ip vpn-instance vpna  
route-distinguisher 2:1  
vpn-target 1:1 export-extcommunity  
vpn-target 1:1 import-extcommunity  
#  
mpls lsr-id 2.2.2.2  
#  
mpls  
#  
mpls ldp  
#  
interface Ethernet0/0  
port link-mode route  
ip address 1.2.0.2 255.255.255.0  
mpls  
mpls ldp  
#  
interface Ethernet0/1  
port link-mode route  
ip binding vpn-instance vpna  
ip address 172.32.0.1 255.255.255.0  
#
```

```
interface LoopBack0
ip address 2.2.2.2 255.255.255.255
#
bgp 1
undo synchronization
peer 1.1.1.1 as-number 1
peer 1.1.1.1 connect-interface LoopBack0
#
ipv4-family vpnv4
peer 1.1.1.1 enable
#
ipv4-family vpn-instance vpna
import-route direct
#
ospf 1
area 0.0.0.0
network 2.2.2.2 0.0.0.0
network 1.2.0.0 0.0.0.255
#
```

四、配置关键点：

1. CEA上需要配置访问其他vpn路由的静态路由；
2. PEA上需要配置访问CEA下挂vpna站点1的静态路由
3. PEA的BGP要引入静态vpna路由。